

CATALOGUE
NETWORK



EN

NETWORK



MEP GROUP

The MEP Group today represents the latest stage in the evolution of the know-how, technology and values that MEP has developed over a period of 50 years.

The MEP Group is present on all major markets and is a leader in those of most importance. The group has production plants in Italy, Canada, the USA and China which produce around 12,000 machines a year. MEP products are sold in over 50 nations around the world thanks to close collaboration with highly qualified local distributors and/or directly controlled subsidiaries (China and Brazil).

The MEP Group's extensive product range satisfies the needs of a wide variety of customers. The range includes manual, numeric control, semi-automatic and fully automatic machines with cutting capacities of up to 1500 mm.



HYDMECH LTD (CANADA)

HYDMECH INC. (USA)

MEP SPA (ITALY)

MEP DO BRASIL LTDA (BRAZIL)

MEP AROUND THE WORLD

MEP (SUZHOU) CO. LTD
(PR. CHINA)



MEP SPA
Pergola (PU)
Italy



MEP DO BRASIL LTDA.
San Paolo - SP
Brazil




MEP (SUZHOU) CO. LTD
Suzhou
P.R. China



HYDMECH
Woodstock, ON
Canada



HYDMECH INC.
Conway, AR
USA



WORKSHOP Enzo Magnani 1959

A FAMILY BUSINESS



The TV 300 was MEP's first series-made abrasive disc cutting machine.

MADE WITH COMMITMENT AND PASSION

The MEP Group has firm roots in one of the many entrepreneurial families that thrive in a region rich in hard-working people, history and art.

It all began in a small workshop in the historical centre of Pergola, a town in the province of Pesaro-Urbino, in the Marche region of Italy.

Enzo Magnani began his career as a mechanic, exploiting the skills he had acquired with British and American forces based in Italy during the Second World War. The ingenuity he showed in his small workshop led to the creation of the first sawing machine, which proved so efficient that it was soon being ordered by small companies working in neighbouring towns. The business really began to expand when Enzo invited his son Ezio, still a young man, to join him.

Ezio, supported on the organisation side by Giampaolo Garattoni, another new partner, began boosting sales and also took over the technical development of products and processes, becoming a key figure for all involved.

Unfortunately, Enzo Magnani passed away at the age of only 52, and never saw the many future achievements of the company he had started.

His death was untimely indeed because the company was just beginning its journey down a road that would see it expand from a local business to a major global competitor, acquiring and forming various other companies to create the MEP Group.



ENZO MAGNANI



EZIO MAGNANI

LEGEND



cutting mode AUTOMATIC



cutting mode SEMI-AUTOMATIC



cutting mode SEMI-AUTOMATIC DYNAMIC



cutting mode MANUAL



ELECTROHYDRAULIC



ELECTROPNEUMATIC



ELECTROMECHANIC



BANDSAWING MACHINES



PH 211-1/HB	03
PH 261-1/HB	04



SHARK 281	05
SHARK 281 CCS	06
SHARK 281 SXI evo	07
SHARK 281 NC 5.0	09
SHARK 282	11
SHARK 282 CCS	12
SHARK 282 SXI evo	13
SHARK 282 NC 5.0	15
SHARK 330 NC 5.0	17
SHARK 331 NC 5.0 spider	19
SHARK 332 CCS	21
SHARK 332 CCS hydra	23
SHARK 332 SXI evo	25
SHARK 332 NC 5.0	27
SHARK 382 CCS hydra	29
SHARK 382 SXI evo	31
SHARK 452-1 CCS	33

SHARK 452-1 CCS hydra	35
SHARK 452-1 SXI evo	37
SHARK 230 NC HS 5.0	38

VERTICAL SAWING MACHINES FOR METALS



TIGER 352/MA	41
TIGER 352 SX evo	43
TIGER 352 NC 5.0	45
TIGER 372 SX evo	47

PIVOT SAWING MACHINES FOR METALS



WILLY 225	49
-----------	----



FALCON 251	50
FALCON 302	51
FALCON 352/MA	52

PIVOT SAWING MACHINES FOR ALUMINIUM



COBRA 352/MA	53
COBRA 352 SX evo	55
COBRA 352 NC 5.0	57

MEASURING SYSTEM



SMV 3000	59
SMV 3000 PRO	60

OPTIONALS	61
TECHNICAL FEATURES	69



PH

211-1

211-1 HB

The PH 211-1, manual band sawing machines for cuts from 0° to 60° on the left are also supplied in a version with HB device to make single cuts





without operators, still keeping the manual cutting cycle available (the HB device is available only in the three-phase version)

HB CUTTING CYCLE

- After positioning the bar and closing the vice, the cutting phase is started, using the weight of the saw frame controlled by a hydraulic circuit to adjust the downfeed speed; after the cut the band stops, the frame is manually lifted in order to reposition the bar to cut until the position needed by the operator , at this point the head frame is locked by the manually-controlled hydraulic valve.

A FEW FEATURES:

- Sturdy structures in cast iron in order to tension the band at 700 kg.
- Electrical board with entirely identifiable wiring, stand-by, main switch with lock, short circuit protection, motor overload cutout, min. voltage coil, low voltage system 24 V.
- Control handle IP55.
- Driving pulley locked with clamp ring to ensure a strong fastening, still allowing axial adjustment.
- Blade-guide heads with 6 CARBIDE pads instead of bearings to ensure a better stability.
- Stop strokes at 0° and 60° on the left with lever for locking at any intermediate angle.
- Head articulation with preloaded tapered bearings.
- Vice with fast locking lever.
- Electric pump for the band lubrication and cooling.
- Brush band-cleaning device.
- Bimetallic band for profiles and solid pieces.
- Instructions manual and spare parts list.











OPTIONALS FROM PAG 61 - N° 02 - 04 - 27 - 28 - 71

mm	kW	m/min	kW	m/min	mm	0°	45°	60°	kg
						180	115	70	
2130x20x0,9	0,75	80	0,70/0,81	40/80	200	180	110	70x70	190



OPTIONALS FROM PAG 61 - N° 02 - 04 - 29 - 30 - 72

								
mm	KW	m/min	mm	0°	225	200	240x160	kg
2450x27x0,9	0,70/0,81	46/92	245	45°	160	140	155x115	
				60°	90	90	90x90	
								240



PH 261-1 261-1/HB



The PH 261-1, manual band sawing machines for cuts from 0° to 60° on the left are also supplied in a version with HB device to make single cuts without operators, still keeping the manual cutting cycle available.



HB CUTTING CYCLE

- After positioning the bar and closing the vice, the cutting phase is started, using the weight of the saw frame controlled by a hydraulic circuit to adjust the downfeed speed; after the cut the band stops, the frame is manually lifted in order to reposition the bar to cut until the position needed by the operator, at this point the head frame is locked by the manually-controlled hydraulic valve.

A FEW FEATURES:

- Sturdy structures in cast iron in order to tension the band at 900 kg.
- Electrical board with entirely identifiable wiring, stand-by, main switch with lock, short circuit protection, motor overload cutout, min. voltage coil, low voltage system 24 V.
- Control handle IP55.
- Driving pulley locked with clamp ring to ensure a strong fastening, still allowing axial adjustment.
- Blade-guide heads with 6 CARBIDE pads instead of bearings to ensure a better stability.
- Stop strokes at 0° and 60° on the left with lever for locking at any intermediate angle.
- Head articulation with preloaded tapered bearings.
- Vice with fast locking lever.
- Electric pump for the band lubrication and cooling.

- Brush band-cleaning device.
- Bimetallic band for profiles and solid pieces.
- Instructions manual and spare parts list.





SHARK 281

SHARK 281, manual band sawing machine to cut from 0° to 60° left.

The vice on the pneumatic versions (MA) opens and closes by means of a manually operated valve (or by means of a footpedal which is instead optional).

A FEW FEATURES:

- Electric panel (wiring totally identifiable, stand-by, loose-key safety switch, main switch, pole change switch, emergency stop, motor magneto-thermal overload, minimum tension coil, protection against missing phase, low tension safety device (LTSD 24 V).- IP55 control handle.
- Vice with fast clamping device.



SHARK 281/281CCS




SHARK 281/281CCS



- Hydraulic transducer to visualize band tensioning.
- Electric pump for band lubrication and cooling.
- Wire chip brush for band cleaning.
- Double head return spring.
- Adjustable rod to measure stop to make cuts of the same length with millimetric steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.
- The CUT CONTROL SYSTEM (CCS) can be retrofitted on machines out in the field.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 07 - 09 - 11 - 16 - 72



mm	kW	m/min	mm	Cross-sections			kg	
				Circle	Square	Rectangle		
2950x27x0,9	1,5/1,8	36/72	285	0°	250	230	280x200	
				45° E	190	180	180x180	
				60° E	120	110	110x110	
								370



SHARK 281 CCS



SHARK 281 CCS (Cut Control System) manual bandsawing machine to cut from 0° up to 60° left. Other than the manual cut mode, the sawing machine can make single cuts without operator, using the head weight control- led by a hydraulic brake: after the cut the band stops. The frame at this point is manually lifted to the position needed in order to reposition the bar to cut. In the version with pneumatic vice (MA) the vice is opened/closed by a manually-controlled valve (optional with pedal control).

A FEW FEATURES: See SHARK 281.



SHARK 281CCS





SHARK 281/281CCS



SHARK 281/281CCS

OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 09 - 11 - 16 - 72

mm	kW	m/min	mm	0°	45°	60°	kg
				250	190	120	
2950x27x0,9	1,5/1,8	36/72	285	230	180	110	370





SHARK 281 SXI EVO

SHARK 281 SXI evo, semi-automatic, electro-hydraulic band sawing machine for cutting from 0° to 60° left.

- Machine with controlled single axis microprocessor with the latest generation of controllers for semi-automatic sawing machines designed by MEP.

OPERATION: starting the cycle by means of the relative push-button, the following steps are carried out: - the vice closes and the motor starts - the head goes down to execute cut - motor stops - head returns to top position and vice opens.

- Standard machine with operation in semi-automatic cycle only, that can be ordered with additional cutting cycles upon request (OPTIONAL): manual and semi-automatic dynamic cycle (semi-automatic dynamic cycle: lowering the head manually, so as to position it just above the material, the semi-automatic cycle starts by pressing trigger switch on handle).

- CYCLE DOWN UP : Operating in semiautomatic cycle, the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.






A FEW FEATURES:



- Console with all centralized controls, installed on an articulated arm.
- Low voltage soft keyboard, in polyester, with thermo-shaped buttons, with tactile feeling and sound signal when operating.
- Display for the following messages: + Diagnostic (messages in the use language). + Alarms (cause description). + Input and output status. + Cut counting. + Time spent for the cut made. + Blade motor absorption + Blade tension. + Blade speed. + Numeric displaying of the head position.- Program with several special cutting cycles.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.

- Double band rotation speed (36/72 m/min) with possibility of ordering the sawing machine with electronic inverter for the continuous adjustment of the band speed (from 15 to 100 m/min).
- The limits of the head stroke are programmed through the console, depending on the dimensions of the bars to be cut.
- Manually-operated blade tensioning through electronic transducer, with displaying.
- Steel base with removable coolant tank.
- Electric pump for band lubrication and cooling.
- Preset to be equipped with the spray mist system (OPTIONAL), other than with the standard-delivered traditional lubrication with emulsible oil.

- Wire chip brush for band cleaning.
- Machine arranged for handling with movement equipment.
- Adjustable rod to measure stop to make cuts of the same length with millimetric steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 11 - 12 - 16 - 32 - 34 - 72



mm	kW	m/min	mm	Blade Width			kg
				0°	45°	60°	
2950x27x0,9	1,5/1,8	36/72	285	250	230	280x200	435
				190	180	180x180	
				120	110	110x110	



SHARK

281 NC 5.0

Shark 281 NC 5.0, electrohydraulic automatic band sawing machine which can operate also in semi-automatic, semi-automatic/dynamic and manual mode to cut from 0° to 60° left.



- CNC machine with a new controller : MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.

A FEW FEATURES:

-7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive , it guarantees a reliable use and it controls all cutting parameters in real time.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 17 - 33 - 34 - 49 - 60 - 72



mm	kW	m/min	mm	0°	45°	60°	kg
				●	■	■	
2950x27x0,9	2,2	15÷100	285	250	190	120	965
				230	180	110	
				280x200	180x180	110x110	



- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position for the controls and the EMERGENCY.
- Visualization and registration of alarms and events with the possibility to visualize the story of occurred events.
- Electronic inverter for the continuous adjustment of the band speed from 15 to 100 m/min.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- Bar feeder with recirculating balls screw/nut and stepper motor (feed in length in one stroke 600 mm, that can be repeated in order to cut any length).
- Cutting head and feeding vice positioning with joystick
- Automatic acquisition of the actual starting point of the cut.
- Electronic transducer to visualize band tensioning.
- Automatic adaptive shearing stress control system with servovalve mounted directly on the cylinder.



- Coolant tank inside the steel base with two electric pumps so as to lubro-refrigerate band. The drawer to collect chips can be replaced with a motorized chip evacuator (see optionals).
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Wire chip brush for band cleaning.
- Machine arranged for handling with movement equipment.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.





SHARK 282



SHARK 282, manual band sawing machine to cut from 45° right to 60° left.

The vice on the pneumatic versions (MA) opens and closes by means of a manually operated valve (or by means of a footpedal which is instead optional).




A FEW FEATURES:

- Hydraulic transducer to visualize band tensioning.
- Wire chip brush for band cleaning.
- Double head return spring.
- Sliding vice with sideways movement and fast-positioning system.
- Wide working surface with rotating table installed on a roller bearing, dia. 265 mm, pre-loaded with thrust bearing.

- Adjustable precision stops for cuts at 0°, 45°, 60° left and 45° right.
- Steel base with removable coolant tray.
- Electric pump for band lubrication and cooling.
- Machine arranged for handling with movement equipment.
- Adjustable rod to measure stop to make cuts of the same length with millimetric steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.
- The CUT CONTROL SYSTEM (CCS) can be retrofitted on machines out in the field.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 08 - 09 - 11 - 20 - 34 - 72



SHARK 282/282CCS

Saw Blade	Power	Speed	Cutting Depth	Cutting Width			Weight
				0°	45°	60°	
2950x27x0,9	1,5/1,8	36/72	285	250	230	120	440
				220	200	80	
				280x220	220x200	140x80	
				200	170	200x140	




SHARK


282 CCS



SHARK 282 CCS (Cut Control System) manual bandsawing machine to cut from 45° right up to 60° left. Other than the manual cut mode, the sawing machine can make single cuts without operator, using the head weight controlled by a hydraulic brake: after the cut, the band stops. The frame at this point is manually lifted to the position needed in order to reposition the bar to cut. In the version with pneumatic vice (MA) the vice is opened/closed by a manually-controlled valve (optional with pedal control).
A FEW FEATURES: See SHARK 282



SHARK 282CCS





SHARK 282/282CCS



SHARK 282/282CCS

OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 09 - 11 - 20 - 34 - 72

mm	kW	m/min	mm	Material			kg
				0°	45°	60°	
2950x27x0,9	1,5/1,8	36/72	285	250	220	280x220	440
				230	200	220x200	
				120	80	140x80	
				200	170	200x140	





SHARK 282 SXI EVO

Shark 282 SXI evo, semi-automatic electro-hydraulic band sawing machine, with operation also in manual and semi-automatic dynamic cycle, for cutting from 45° right to 60° left.

- Machine with controlled single axis microprocessor with the latest generation of controllers for semi-automatic sawing machines designed by MEP.

- Semi-automatic cycle: Starting the cycle: - the vice closes and the motor starts – the head goes down to execute cut – motor stops – head returns to top position and vice opens.

- Semi-automatic dynamic cycle: lowering the head manually, so as to position it just above the material, the semi-automatic cycle starts by pressing trigger switch on handle.

- CYCLE DOWN UP : Operating in semiautomatic cycle , the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.





A FEW FEATURES:



- Console with all centralized controls, installed on an articulated arm.
- Low voltage soft keyboard, in polyester, with thermo-shaped buttons, with tactile feeling and sound signal when operating.
- Display for the following messages: + Diagnostic + Allarms (cause description). + Input and output status. + Cut counting. + Time spent for the cut made. + Blade motor absorption. + Blade tension. + Blade speed. + Numeric displaying of the head position.
- Control handle of the manual cycle at 24 V, IP55.
- Program with several special cutting cycles.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.

- Wide working surface with rotating table installed on a roller bearing, dia. 265 mm, pre-loaded with thrust bearing.
- Double band rotation speed (36/72 m/min) with card PRESET to mount the electronic inverter for the continuous adjustment of the band speed (from 15 to 100 m/min).
- The limits of the head stroke are programmed through the control board, depending on the dimensions of the bars to be cut.
- Manually-operated blade tensioning through electronic transducer, with displaying.
- Steel base with removable coolant tray.
- Electric pump for band lubrication and cooling.
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-

- delivered traditional lubrication with emulsible oil.
- Wire chip brush for band cleaning.
- Machine arranged for handling with movement equipment.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 11 - 12 - 20 - 32 - 34 - 72



mm	kW	m/min	mm	Cross-section			kg	
				Circle	Square	Rectangle		
2950x27x0,9	1,5/1,8	36/72	285	0°	250	220	280x220	
				45°	230	200	220x200	
				60°	120	80	140x80	
				45°	200	170	200x140	475



SHARK

282 NC 5.0


SHARK 282 NC 5.0, electro-hydraulic automatic band sawing machine which can operate also in semi-automatic, semi-automatic/dynamic and manual mode.

- Automatic cycle cut from 0° to 60° left
- Semi-automatic, semi-automatic/dynamic and manual cycle (for cuts from 45° right to 60° left).
- CNC machine with a new controller : MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.




OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 21 - 33 - 34 - 37 - 50 - 60 - 72

SHARK 282 NC 5.0



mm	kW	m/min	mm	Cuts				mm	mm	mm	kg				
				0°	45°	60°	45°								
2950x27x0,9	2,2	15+100	285	250	230	120	200	220	200	80	280x220	220x200	140x80	200x140	990



A FEW FEATURES:

- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position for the controls and the EMERGENCY.
- 7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive, it guarantees a reliable use and it controls all cutting parameters in real time.
- Visualization and registration of alarms and events with the possibility to visualize the story of occurred events.
- Electronic inverter for the continuous adjustment of the band speed from 15 to 100 m/min.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- Bar feeder with recirculating balls screw/nut and stepper motor (feed in length in one stroke 600 mm, that can be repeated in order to cut any length).
- Cutting head and feeding vice positioning with joystick.

- Automatic acquisition of the actual starting point of the cut.
- Electronic transducer to visualize band tensioning.
- Automatic adaptive shearing stress control system with servovalve mounted directly on the cylinder.
- Coolant tank inside the steel base with two electric pumps so as to lube-refrigerate band. The drawer to collect chips can be replaced with a motorized chip evacuator (see optionals).
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Wire chip brush for band cleaning.
- Machine arranged for handling with movement equipment.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.





SHARK 330 NC 5.0

SHARK 330 NC 5.0, electrohydraulic automatic band sawing machine which can operate also in semi-automatic cycle to cut at 0° with restpiece which cannot be fed in automatic of 85 mm.



- CNC machine with a new controller : MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.










A FEW FEATURES:

-7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive , it guarantees a reliable use and it controls all cutting parameters in real time.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 19 - 33 - 34 - 51 - 60 - 72



								
mm	kW	m/min	mm	0°	300	250	330x250	kg
3320x27x0,9	2,2	15÷100	335					1025



- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position for the controls and the EMERGENCY.
- Visualization and registration of alarms and events with the possibility to visualize the story of occurred events.
- Electronic inverter for the continuous adjustment of the band speed from 15 to 100 m/min.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- Feeder operated by stepper motor with screw mounted on preloaded taper bearings and nut with recirculating ballscrews (feed in length in one stroke: 600 mm).
- Automatic acquisition of the actual starting point of the cut.
- Electronic transducer to visualize band tensioning.
- Cutting head and feeding vice positioning with joystick
- Automatic adaptive shearing stress control system with servovalve mounted directly on the cylinder.
- Adjustable rollers for bundle cutting on one row.
- Adjustable guide to unload cut pieces.
- Coolant



- tank inside the steel base with two electric pumps so as to lube-refrigerate band. The drawer to collect chips can be replaced with a motorized chip evacuator (see optionals).
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Motorized wire chip brush for band cleaning.
- Machine arranged for handling with movement equipment.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list in the language of use.





SHARK

331 NC 5.0 SPIDER

SHARK 331 NC 5.0 spider, Electrohydraulic automatic band sawing machine which can also operate in semi-automatic cycle for cuts from 0° up to 60° left.

Machine with compact dimensions.



CNC machine with a new controller: MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.

A FEW FEATURES:

- 7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive, it guarantees a reliable use and it controls all cutting parameters in real time.
- Console with all centralized controls, installed on a fixed pedestal in order that the operator can operate all programming and operating functions completely safe.
- Visualization and registration of alarms and events with the possibility to visualize the story of occurred events.
- Visualization and registration of alarms and events with the possibility to visualize the story of occurred events.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 17 - 33 - 34 - 51 - 61



m/min	kW	mm	OIL		mm		Kg	0°	45°	60°	280	260	330x260
			kW	l	mm	mm							
15÷100	2,2	3320x27x0,9	0,75	33	0,18	100	340	1240	260	170	270x200	170x170	



- Electronic inverter for the continuous adjustment of the band speed from 15 to 100 m/min.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- Bar feeder with recirculating balls screw/nut and stepper motor (feed in length in one stroke 600 mm, that can be repeated in order to cut any length).
- Feeding vice cover with safety limit switch in case the operator opens the cover during the cutting cycle.
- Cutting head and feeding vice positioning with joystick.
- Automatic acquisition of the actual starting point of the cut.
- Electronic transducer to visualize band tensioning.

- Automatic adaptive shearing stress control system with servovalve mounted directly on the cylinder.
- Continuous control of the blade rotation. In case the blade is jammed, automatically the machine will stop.
- Adjustable rollers for bundle cutting on one row.
- Adjustable guide to unload cut pieces.
- Extractable coolant tank with two electric pumps so as to lube-refrigerate band. The drawer to collect chips can be replaced with a motorized chip auger (OPTIONAL).
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.

- Additional foot pedal with emergency stop (OPTIONAL).
- Wire chip brush for band cleaning.
- Emergency lamp with acoustic signal in case the machine is in a stand still situation.
- Machine arranged for handling with movement equipment.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list in the language of use.





SHARK 332 CCS

SHARK 332 CCS, manual band sawing machine to cut from 60° left to 45° right. This model is available in the manual version or with the Cut Control System (CCS).

- Functioning of the CCS cycle: after positioning the bar and closing the vice, the cutting phase is started, using the weight of the saw head controlled by a hydraulic braking circuit to adjust the feeding speed; after the cut, the saw head is manually lifted till the position needed for the bar to be fed.

In the Shark 332 CCS MA model (pneumatic vice) vice opens/closes by means of a footpedal.






A FEW FEATURES:

- Electric system (wiring totally identifiable, stand-by, main lockable disconnect switch, pole change switch, emergency stop, motor magneto-thermal overload, minimum tension coil, protection against missing phase, low tension safety device 24 V).
- Band tensioning with visualization on LCD by electronic transducer.




- Manual clamping system by means of vice screw with fast-positioning system.
- Coolant tank inside the steel base and drawer to collect chips which can be replaced with a motorized chip evacuator (see optionals).
- Electric pump for band lubrication and cooling.
- Wire chip brush for band cleaning.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.

- Machine arranged for handling with movement equipment.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 11 - 12 - 20 - 34 - 65 - 72

mm	kW	m/min	mm	0°	45°	60°	45°	kg
3320x27x0,9	1,5/1,8	40/80	335	300	260	180	200	640
				330x260	270x200	170x170	200x160	





SHARK

332 CCS HYDRA

SHARK 332 CCS hydra, band sawing machine for single cuts without operator from 60° on the left to 45°.

CUTTING CYCLE

- After positioning the bar, operate through the new console to access the following controls:

- vice closing

- starting the cutting cycle that uses the weight of the head controlled by a hydraulic braking circuit to adjust the feeding speed.

After the cut, by the keyboard controls, the operator lifts the head through a hydraulic control unit till the necessary position and opens again the pneumatic vice to enable a new bar feeding.







A FEW FEATURES:

- Electrical system (entirely identifiable wiring, stand-by, main switch with lock, motor switch, emergency device, motor overload cutout, min. voltage coil, phase shortage protection, low voltage system 24 V).
- Rotating table (installed on a roller bearing, diameter 420 mm, pre-loaded with thrust bearing) complete with replaceable steel plates on the working surface.
- Double band rotation speed 40/80 m/min (OPTIONAL 20/40 m/min)
- Electronic transducer for the band tensioning with displaying on the console.



- Pneumatic vice with fast approach device.
- Stand with coolant tank and chip tray that can be replaced with a motor-driven chip extractor (OPTIONAL).
- Electric pump (or hydraulic OPTIONAL) for the band lubrication and cooling.
- Machine preset to be equipped with the blade minimal lubrication kit (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsifiable oils.
- Brush band-cleaning device.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.

- Machine preset for being handled by transpallet.
- Bimetallic band for profiles and solid pieces.
- Service keys and instructions manual, for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 11 - 12 - 20 - 34 - 65 - 72

mm	kW	m/min	mm	Blade shapes			kg
				0°	45°	60°	
3320x27x0,9	1,5/1,8	40/80	335	300	260	330x260	670
				260	250	270x200	
				180	170	170x170	
				200	180	200x160	





SHARK 332 SXI EVO

SHARK 332 SXI evo, semi-automatic electro-hydraulic sawing machine , with operation also in manual and semi-automatic dynamic cycle, for cutting from 45° right to 60° left.

- Machine with controlled single axis microprocessor with the latest generation of controllers for semi-automatic sawing machines designed by MEP.

- Semi-automatic cycle: starting the cycle: - the vice closes and the motor starts – the head goes down to execute cut – motor stops – head returns to top position and vice opens.

- Semi-automatic dynamic cycle: lowering the head manually, so as to position it just above the material, the semi-automatic cycle starts by pressing trigger switch on handle.

- CYCLE DOWN UP : Operating in semiautomatic cycle , the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.







A FEW FEATURES:


- Console with all centralized controls, installed on an articulated arm.
- Low voltage soft keyboard, in polyester, with thermo-shaped buttons, with tactile feeling and sound signal when operating.
- Display for the following messages: Diagnostic + Allarms (cause description). + Input and output status. + Cut counting. + Time spent for the cut made. + Blade motor absorption. + Blade tension. + Blade speed. + Numeric displaying of the head position.
- Control handle of the manual cycle at 24 V, IP55.
- Program with several special cutting cycles.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- Rotating table (mounted on a 420 mm roller bearing, pre-loaded with thrust bearing) with steel vice plates which can be replaced after wear.- Double band rotation speed (40/80 m/min) with card PRESET to mount the electronic inverter for the continuous adjustment of the band speed (from 15 to 100 m/min).
- The limits of the head stroke are programmed through the control board, depending on the dimensions of the bars to be cut.
- Sliding vice with sideways movement and fast-positioning system which functions in automatic also when in manual mode.

- Manually-operated blade tensioning through electronic transducer, with displaying.
- Steel base allows to recover coolant also when cutting at the maximum degrees.
- Coolant tank inside the steel base with electric pump so as to lube-refrigerate band. The drawer to collect chips can be replaced with a motorized chip evacuator (see optionals).
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Wire chip brush for band cleaning.


- Machine arranged for handling with movement equipment.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 11 - 12 - 20 - 32 - 34 - 55 - 66 - 72



mm	kW	m/min	mm	Shape			kg
				0°	45°	60°	
3320x27x0,9	1,5/1,8	40/80	335	300	260	330x260	670
				260	250	270x200	
				180	170	170x170	
				200	180	200x160	





SHARK

332 NC 5.0



SHARK 332 NC 5.0, electrohydraulic band sawing machine with multimicroprocessor which can operate in automatic, semi-automatic, semi-automatic/dynamic and manual mode.

- Automatic cycle (to cut from 0° to 60° left)
- Semi-automatic, semi-automatic/dynamic and manual cycle (for cuts from 45° right to 60° left).
- CNC machine with a new controller : MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.




OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 21 - 33 - 34 - 35 - 36 - 37 - 52 - 55 - 60 - 66 - 72

SHARK 332 NC 5.0



mm	kW	m/min	mm	Cutting direction				Workpiece size			kg
				0°	45°	60°	45°	Circle	Square	Rectangle	
3320x27x0,9	2,2	15÷100	335	0°	45°	60°	45°	300	260	330x260	1105
				45°	60°	45°	260	250	270x200		
				60°	45°	200	180	170	170x170		
				45°	200	180	200x160				




A FEW FEATURES:

- 7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive, it guarantees a reliable use and it controls all cutting parameters in real time
- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position for the controls and the EMERGENCY.
- Visualization and registration of alarms and events with the possibility to visualize the story of occurred events.
- Electronic inverter for the continuous adjustment of the band speed from 15 to 100 m/min.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- Bar feeder with recirculating balls screw/nut and stepper motor (feed in length in one stroke 600 mm, that can be repeated in order to cut any length).
- Cutting head and feeding vice positioning with joystick



- Automatic acquisition of the actual starting point of the cut.
- Electronic transducer to visualize band tensioning.
- Automatic adaptive shearing stress control system with servovalve mounted directly on the cylinder.
- Coolant tank inside the steel base with two electric pumps so as to lube-refrigerate band. The drawer to collect chips can be replaced with a motorized chip evacuator (see optionals).
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Wire chip brush for band cleaning.
- Machine preset for being handled by transpallet.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.





SHARK

382 CCS HYDRA

SHARK 382 CCS hydra, band sawing machine for single cuts without operator from 60° on the left to 45°.

CUTTING CYCLE

- After positioning the bar, operate through the new console to access the following controls:

- vice closing

- starting the cutting cycle that uses the weight of the head controlled by a hydraulic braking circuit to adjust the feeding speed.

After the cut, by the keyboard controls, the operator lifts the head through a hydraulic control unit till the necessary position and opens again the pneumatic vice to enable a new bar feeding.







A FEW FEATURES:

- Electrical system (entirely identifiable wiring, stand-by, main switch with lock, motor switch, emergency device, motor overload cutout, min. voltage coil, phase shortage protection, low voltage system 24 V).
- Rotating table (installed on a roller bearing, diameter 420 mm, pre-loaded with thrust bearing) complete with replaceable steel plates on the working surface.
- Double band rotation speed 40/80 m/min (OPTIONAL 20/40 m/min)
- Electronic transducer for the band tensioning with displaying on the console.



- Pneumatic vice (or hydraulic OPTION)with fast approach device.
- Stand with coolant tank and chip tray that can be replaced with a motor-driven chip extractor (OPTIONAL).
- Electric pump for the band lubrication and cooling.
- Machine preset to be equipped with the blade minimal lubrication kit (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsifiable oils.
- Brush band-cleaning device.
- Adjustable rod to measure stop to make cuts of

- the same length with millimetred steel rod.
- Machine preset for being handled by transpallet.
- Bimetallic band for profiles and solid pieces.
- Service keys and instructions manual, for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 11 - 12 - 21 - 34 - 65 - 74

mm	kW	m/min	mm	Cross-section			kg	
				Circle	Square	Rectangle		
3440x27x0,9	1,5/1,8	40/80	385	0°	280	260	380x260	
				45°	260	250	270x200	
				60°	180	170	170x170	
				45°	200	180	200x160	695





SHARK 382 SXI EVO

SHARK 382 SXI evo, semi-automatic electro-hydraulic sawing machine , with operation also in manual and semi-automatic dynamic cycle, for cutting from 45° right to 60° left.

- Machine with controlled single axis microprocessor with the latest generation of controllers for semi-automatic sawing machines designed by MEP.

- Semi-automatic cycle: starting the cycle: - the vice closes and the motor starts – the head goes down to execute cut – motor stops – head returns to top position and vice opens.

- Semi-automatic dynamic cycle: lowering the head manually, so as to position it just above the material, the semi-automatic cycle starts by pressing trigger switch on handle.

- CYCLE DOWN UP : Operating in semiautomatic cycle , the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.







A FEW FEATURES:



- Console with all centralized controls, installed on an articulated arm.
- Low voltage soft keyboard, in polyester, with thermo-shaped buttons, with tactile feeling and sound signal when operating.
- Display for the following messages: Diagnostic + Allarms (cause description). + Input and output status. + Cut counting. + Time spent for the cut made. + Blade motor absorption. + Blade tension. + Blade speed. + Numeric displaying of the head position.
- Control handle of the manual cycle at 24 V, IP55.
- Program with several special cutting cycles.
- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- Rotating table (mounted on a 420 mm roller bearing, pre-loaded with thrust bearing) with steel vice plates which can be replaced after wear.- Double band rotation speed (40/80 m/min) with card PRESET to mount the electronic inverter for the continuous adjustment of the band speed (from 15 to 100 m/min).
- The limits of the head stroke are programmed through the control board, depending on the dimensions of the bars to be cut.
- Sliding vice with sideways movement and fast-positioning system which functions in automatic also when in manual mode.

- Manually-operated blade tensioning through electronic transducer, with displaying.
- Steel base allows to recover coolant also when cutting at the maximum degrees.
- Coolant tank inside the steel base with electric pump so as to lube-refrigerate band. The drawer to collect chips can be replaced with a motorized chip evacuator (see optionals).
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Wire chip brush for band cleaning.


- Machine arranged for handling with movement equipment.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 11 - 12 - 21 - 32 - 34 - 55 - 66 - 74



mm	kW	m/min	mm	0°	45°	60°	45°	kg
3440x27x0,9	1,5/1,8	40/80	385	280	260	180	200	695





SHARK 452 -1 CCS

SHARK 452-1 CCS, sawing machine for single cuts without operator with 4500x34x1,1 mm band, for cutting pipes, profiles and beams up to 450x320 mm at 0°.

- Extremely versatile machine, for cuts between 60° left and 60° right.

CUTTING CYCLE:

- after positioning the bar and closing the vice, the cutting phase is started, using the weight of the saw head controlled by a hydraulic braking circuit to adjust the feeding speed; after the cut, the saw head is manually lifted till the position needed for the beam to be fed.






A FEW FEATURES:



- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position.
- DISPLAY for the blade tensioning.
- Electronic inverter for the continuous adjustment of the band speed from 15 to 100 m/min.
- Rotating table, with etched accuracy graduation, tilting on a roller bearing with 280-mm diameter.
- Wide supporting surface for the max. safety and stability while cutting.
- The bar support with roller, on the left of the cutting table, slides on linear guide with ball








- recirculation, so that it can be easily moved to cut up to the max. angles without any disassembly.
- Manual vice with fast sliding approach, movable on linear guides with ball recirculation.
- Manually-operated blade tensioning through electronic transducer.
- Vertical support of the movable head with manual adjustment, sliding on linear guide with ball recirculation.
- Wire chip brush.
- Electric pump for the band lubrication and cooling.
- Coolant pistol to keep working surfaces clean.

- Coolant tank inside the steel base and chip drawer.
- Machine arranged for handling with lifter.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 22 - 23 - 34 - 65 - 74



									
	mm	kW	m/min	mm	kg				
						0°	330	320	450x320
						45°	320	300	300x300
						60°	210	200	200x200
						45°	320	300	300x300
						60°	210	200	200x200
452-1 CCS	4500x34x1,1	4,0	15÷100	455	1140				



SHARK

452-1 CCS HYDRA

SHARK 452-1 CCS HYDRA, band sawing machine for single cuts without operator on pipes, profiles and beams, up to 450x320 mm at 0°.

Extremely versatile machine, for cuts between 60° on the left and 60° on the right.

CUTTING CYCLE

- After positioning the bar, operate through the new console to access the following controls:
- vice closing
- starting the cutting cycle that uses the weight of the arc controlled by a hydraulic braking circuit to adjust the feeding speed.

After the cut, by the keyboard controls, the operator lifts the head through a hydraulic control unit till the necessary position and opens again the pneumatic vice to enable a new bar feeding.





A FEW FEATURES:



- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position.
- Display for the blade tensioning.
- Electronic inverter for the continuous adjustment of the band speed (from 15 to 100 m/min).
- Rotating table, with etched precision grading, installed on a roller bearing, diameter 280 mm
- System with encoder for reading and displaying the cutting angle (OPTIONAL)
- Wide supporting surface to guarantee safety and stability while cutting.









- Bar support with rollers, on the left of the cutting plane, sliding on linear guide with ball recirculation, so that it can be easily moved to cut up to the max. angles without any disassembly.
- Pneumatic vice (or hydraulic OPTION) with fast sliding approach, movable on linear guides with ball recirculation.
- Vertical support of the movable head with manual adjustment, sliding on linear guide with ball recirculation. - Brush band-cleaning device.
- Electric pump for the band lubrication and cooling.

- Machine preset to be equipped with the blade minimal lubrication kit (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsifiable oils.
- Gun for the working table washing.
- Coolant tank incorporated in the stand and chip tray.
- Machine preset for being handled by lifter.
- Bimetallic band for profiles and solid pieces.
- Service keys and instructions manual, for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 22 - 23 - 34 - 65 - 74



									
	mm	kW	m/min	mm	kg				
						0°	330	320	450x320
						45°	320	300	300x300
						60°	210	200	200x200
						45°	320	300	300x300
452-1 CCS hydra	4500x34x1,1	4,0	15÷100	455	1140	60°	210	200	200x200



SHARK

452-1 SXI EVO

SHARK 452-1 SXI evo, semi-automatic electro-hydraulic sawing machine with 4500x34x1,1 mm band, to cut pipes, profiles and beams up to 450x320 mm at 0°.

- Extremely versatile machine, for cuts between 60° left and 60° right.

CUTTING CYCLE:

after having positioned the bar, starting the cycle the following operations are performed: vice closing - motor start - head descent for cutting - motor stop - head return - vice opening.

- CYCLE DOWN UP : Operating in semiautomatic cycle, the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.

A FEW FEATURES:

- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position for the controls and the EMERGENCY.






- Latest generation hydraulic control unit, with high efficiency and low energy consumption.
- The headstroke, according to the dimensions of the material which has to be cut, is set directly from the control panel.
- Low voltage soft keyboard, in polyester, with thermo-shaped buttons, with tactile feeling and sound signal when operating.
- Display for the following messages: + diagnostic + alarms (cause description) + input and output status + cut counting + time spent for the cut made + blade motor absorption + blade tension + blade speed + numeric displaying of the head position.-
- Electronic inverter for the continuous adjustment of the band speed from 15 to 100 m/min.









- Rotating table, with etched accuracy graduation, tilting on a roller bearing with 280-mm diameter.
- Wide supporting surface for the max. safety and stability while cutting.
- The bar support with roller, on the left of the cutting table, slides on linear guide with ball recirculation, so that it can be easily moved to cut up to the max. angles without any disassembly.
- Hydraulic vice with fast sliding approach, movable on linear guides with ball recirculation.
- Manually-operated blade tensioning through electronic transducer.
- Vertical support of the movable head with manual adjustment, sliding on linear guide with ball recirculation.

- Wire chip brush.
- Electric pump for the band lubrication and cooling.
- Coolant pistol to keep working surfaces clean.
- Coolant tank inside the steel base and chip drawer.
- Machine arranged for handling with lifter.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 10 - 22 - 23 - 32 - 34 - 66 - 69 - 74



									
	mm	kW	m/min	mm	kg				
						0°	330	320	450x320
						45°	320	300	300x300
						60°	210	200	200x200
						45°	320	300	300x300
452-1 SXI evo	4500x34x1,1	4,0	15÷100	455	1140	60°	210	200	200x200



SHARK

230 NC HS 5.0


SHARK 230 NC HS 5.0, electrohydraulic automatic double-column bandsaw for 0° cuts on profiles and solid parts in structural, stainless and alloy steels, with restpiece which cannot be fed in automatic of 60 mm.

- It cuts dimensions up to 230x230 mm and can operate also in semi-automatic cycle.
- CNC machine with controlled double axis so as to obtain, on the same bar, 1000 different lots each of different lengths and quantities.
- CNC machine with a new controller : MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.



OTHER FEATURES

- 7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive, it guarantees a reliable use and it controls all cutting parameters in real time
- Protective guards for the operator safety according to the latest Machine Directives EN 13898/2007.
- Field bus control system with double microprocessor with serial connection.
- Structure in sturdy cast iron G25, to absorb vibrations and give the machine a better cutting stability and longer blade life.
- Ergonomically positioned on the front side of the machine, the control panel allows for easy viewing of machine operations and job set up.
- Infinitely adjustable cutting speed from 15 to 100 m/min controlled by an AC inverter drive system.
- Automatic acquisition of the actual starting point of the cut



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 34 - 53 - 54 - 61 - 72 - 73



mm	kW	mm	kW	l	kW	l	mm	mm	mm	kg	
15±100	2,2	2950x27x0,9	0,75	33	0,18	95	255	0°	230	230	1000



- Saw frame movement on linear guide with ball-recirculating pre-charged slide.
- Cutting head and feeding vice positioning with joystick
- Automatic adaptive shearing stress control system with servovalve mounted directly on the cylinder.
- Manual band tension with LED display on control panel.
- Hydraulic power pack to supply the saw frame and the feeding and cutting vices. Variable pressure adjusters allow to set the clamping force.
- Feeding length up to 500 mm in a single stroke driven by a stepper motor and ball screw assembly.
- Feeder vice with sideways movement for self-adjustment in case of bars slightly deformed.
- Automatic retract of back jaw feeder vice to help the feed-in of bars heavily deformed (OPTIONAL).

- Driving pulley secured by tapered hub to ensure a strong fastening still allowing axial adjustment.
- Adjustable blade-guide heads in steel with carbide guide inserts, coolant taps for the traditional lubrication and preset to install the mist lubrication (OPTIONAL).
- Automatic adjustment of the front blade-guide head according to the dimensions of the bars to be cut.
- Two vertical rollers to help aligning the material.
- Adjustable guide to unload cut pieces.
- Band rotation control with stop in real time in case of locked tool.
- Enclosed steel base with coolant tank and chip drawer, that can be replaced by a powered chip auger (OPTIONAL).
- Blade brush driven off band wheel.
- Sound and flashing indicator for machine shut-downs.

- Machine preset for being handled by lift truck or crane.
- Bimetal band for the cut of profiles and solid pieces.
- Service keys and instructions manual, for maintenance and spare parts list.





TIGER

352 / 352 MA

TIGER 352, manual vertical sawing machine to cut from 60° left to 45° right, with HSS blade.

A FEW FEATURES:

- Sawing head movement on double linear guides with preloaded slides with recirculating ballscrews.
- Electrical panel (wiring totally identifiable, main lockable disconnect switch, motor magneto-thermal overload, minimum tension coil, protection against missing phase, low tension safety device 24 V).








- Low voltage IP55 control handle.
- Rotating table on a center pin with axial bearing which allows higher precision on the cutting angle set.
- Double set of gears to obtain a high performance.
- Four speeds blade rotation 15/30/45/90 rpm (OPTIONAL 30/60/90/180 rpm).
- Vice with anti-burr device with double clamping of the piece.
- Wire chip brush for band cleaning.

- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Steel base with chip drawer and removable coolant tray.
- Electrical pump for the blade lubrication and cooling.
- The machine is supplied without saw blade.

- Service keys and instructions manual for maintenance and spare parts list.
- The vice on the TIGER 352 MA (pneumatic vice) opens and closes by means of a manually operated valve (or by means of a footpedal which is instead optional).



OPTIONALS FROM PAG 61 - N° 02 - 03 - 05 - 09 - 13 - 26 - 39 - 43 - 71



HSS	kW	rpm	mm	∅	○	□	▭	∅	■	kg
350x32x2,5	1,8/2,5	15/30/45/90	190	350	115	95	180x95	350	90	
				350	110	95	125x95	350	64	
				350	90	90	90x90	350	45	
				350	110	95	125x95	350	64	375



TIGER 352 SX EVO

TIGER 352 SX evo, semi-automatic vertical sawing machine to cut steels from 60° left to 45° right, with HSS blade.

- Machine with controlled single axis microprocessor with the latest generation of controllers for semi-automatic sawing machines designed by MEP.

OPERATION: starting the cycle by means of the relative push-button, the following steps are carried out: - the vice closes and the motor starts – the head goes down to execute cut – motor stops – head returns to top position and vice opens.

- CYCLE DOWN UP : Operating in semiautomatic cycle , the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.

A FEW FEATURES:

- Panel with low tension controls: polyester membrane keypad with tactile thermo-shaped buttons which give out an acoustic signal when pressed.







- Display: 16 characters read on two lines so as to visualize technological parameters such as: + number of cuts programmed and carried out + cutting time + amperometer + diagnostics and/or caution messages (more than 100) visualized.
- Registration of alarms and events with the possibility to visualize the story of occurred events.
- The headstroke, according to the dimensions of the material which has to be cut, is set directly from the control panel.
- Double set of gears to obtain a high performance.- Four speeds blade rotation 15/30/45/90 rpm (OPTIONAL 30/60/90/180 rpm).

- Sawing head movement on double linear guides with preloaded slides with recirculating ballscrews.
- Coaxial cylinder with bypass valve for fast approach and linear transducer for head position reading.
- Rotating table on a center pin with axial bearing which allows higher precision on the cutting angle set.
- Pneumatic vertical vice.
- Steel base with chip drawer and removable coolant tray.
- Electric pump for the blade lubrication and cooling.


- Wire chip brush for band cleaning.
- HSS blade \varnothing 350x32x2.5 for solids or sections.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 05 - 10 - 13 - 26 - 43 - 44 - 45 - 71



HSS	kW	rpm	mm	∅	○	□	▭	∅	■	kg
350x32x2,5	1,8/2,5	15/30/45/90	190	350	115	95	180x95	350	90	
				350	110	95	125x95	350	64	
				350	90	90	90x90	350	45	
				350	110	95	125x95	350	64	410





TIGER 352 NC 5.0

TIGER 352 NC 5.0, electro-pneumatic automatic vertical sawing machine which can operate also in semi-automatic mode, to cut from 60° left to 45° right, with HSS blade.

-CNC machine with a new controller : MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.

A FEW FEATURES:

- 7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive , it guarantees a reliable use and it controls all cutting parameters in real time

- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position for the controls and the EMERGENCY.








- Registration of alarms and events with the possibility to visualize the story of occurred events.
- Bar feeder with recirculating balls screw/nut and stepper motor (feed in length in one stroke 600 mm, that can be repeated in order to cut any length).
- Electronic inverter for the continuous adjustment of the band speed from 15 to 90 rpm (OPTIONAL 30 to 150 rpm).
- Panel with low tension controls: polyester membrane keypad with tactile thermo-shaped buttons which give out an acoustic signal when pressed.
- Double set of gears to obtain a high performance.
- Sawing head movement on double linear

- guides with preloaded slides with recirculating ballscrews.
- Coaxial cylinder with bypass valve for fast approach and linear transducer for head position reading.
- Cutting head and feeding vice positioning with joystick
- Automatic acquisition of the actual starting point of the cut
- Shearing stress control.
- Rotating table on a center pin with axial bearing which allows higher precision on the cutting angle set.
- Pneumatic vertical vice.
- Electric pump for the blade lubrication and

- cooling.
- Wire chip brush for band cleaning.
- Indicator with flashing light in case cycle is stopped.
- HSS blade $\varnothing 350 \times 32 \times 2.5$ for solids or sections.
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 05 - 10 - 26 - 40 - 41 - 42 - 43 - 56 - 71



HSS	kW	rpm	mm	0°	∅	○	□	▭	∅	■	kg
					mm	mm	mm	mm	mm	mm	
350x32x2,5	3,0	15±90	190	45°	350	110	95	125x95	350	64	685
				60°	350	90	90	90x90	350	45	
				45°	350	110	95	125x95	350	64	





TIGER 372 SX EVO

TIGER 372 SX evo, semi-automatic vertical sawing machine to cut steels from 60° left to 45° right, with HSS blade.

- Machine with controlled single axis microprocessor with the latest generation of controllers for semi-automatic sawing machines designed by MEP.

OPERATION: Starting the cycle by means of the relative push-button the following steps are carried out: - the vice closes and the motor starts - the head goes down to execute cut - motor stops - head returns to top position and vice opens.

- CICLE DOWN UP : Operating in semiautomatic cycle , the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.

A FEW FEATURES:

- Panel with low tension controls: polyester membrane keypad with tactile thermo-shaped buttons which give out an acoustic signal when pressed.








- Display: 16 characters read on two lines so as to visualize technological parameters such as: + band speed + number of cuts programmed and carried out + cutting time + amperometer + diagnostics and/or caution messages (more than 100) visualized.
- Registration of alarms and events with the possibility to visualize the story of occurred events.
- Transmission system at 3 stages to guarantee high sturdiness, precision and obtain high removal capacities.
- Blade rotation with one speed motor with electronic speed variator so as to cut from 15 up to 150 rpm to obtain the best cutting efficiency.
- Sawing head movement on double linear guides with preloaded slides with recirculating ballscrews.
- Coaxial cylinder with bypass valve for fast approach and linear transducer for head position reading.
- The headstroke, according to the dimensions of the material which has to be cut, is set directly from the control panel.

- Rotation pin with preloaded thrust bearing to grant rotation precision and stability.
- Accuracy graduation etched on the rotating table.
- Easily movable vice unit with fast, safe and accurate locking on the whole machine width.
- Pneumatic locking vice with adjustable steel gib.
- Pneumatic vertical vice.
- Wire chip brush for band cleaning.
- Steel base with chip drawer and removable coolant tray.
- Electric pump for the blade lubrication and cooling.

- Anti-burr device with double locking system of the stock.
- HSS blade Ø 350x32x2.5 for solids or sections.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 05 - 10 - 26 - 43 - 44 - 45 - 71



HSS	inverter		mm	mm	∅	○	□	▭	●	■	▬	kg
	mm	kW										
370x32x3	5,5	15÷90	190	0°	370	120	110	180x100	120	110	180x100	
				45°	370	115	100	120x100	70	70	70x70	
				60°	370	115	90	90x90	50	50	50x50	
				45°	370	115	100	100x100	70	70	70x70	615





WILLY 225


WILLY 225, small sawing machine, bench model, with HSS blade, to cut from 0° to 45° left. Model for hobbyists and fitters, entirely built in cast iron and available in 1-speed single-phase version.











A FEW FEATURES:

- Bronze gear and casehardened/grounded worm screw which work immersed in oil.- The head which swivels is locked by means of a screw so as to mitre cut.
- Control handle IP55 with 20-A microswitch to start/stop blade.
- Coolant system with membrane pump and coolant tank.
- Adjustable stop to make cuts of the same length.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 05



									
mm	kW	rpm	mm	0°	∅	∅	∅	∅	kg
HSS 225x32x1,9	0,7	50	70	45° 	225	65	60	225	30
					225	55	50	225	38



FALCON 251



FALCON 251, small manual pivot sawing machine to cut metals from 0° to 45° left, using an HSS blade. Practical and safe to use, it can be supplied as a bench model or with the steel base, with three-phase or single-phase speed motor.

- Electric submerged pump at 48 V to lubro-refrigerate blade.
- Adjustable stop to make cuts of the same length.
- The machine is supplied without saw blade.
- Service keys and instructions manual for maintenance and spare parts list.



A FEW FEATURES:

- Electric system: wiring totally identifiable, motor switch, low tension safety device (LTSD 24 V) with IP55 control handle for the three-phase version and IP55 control handle for the single-phase version.
- Metal blade cover which totally encloses the blade.
- Double head return spring.
- Bronze gear and casehardened/grounded worm screw which work immersed in oil.
- Vice with anti-burr device with double clamping of the piece.



OPTIONALS FROM PAG 61 - N° 02 - 05 - 64

mm	kW	rpm	mm	0°	250	70	60	90x50	225	30	kg
HSS 250x32x2	0,5	45	105	45°	250	65	55	70x45	225	20	76





FALCON 302



FALCON 302, manual sawing machine to cut metals from 45° right to 45° left using an HSS blade. This high performance model has a heavy cast iron structure and is equipped with all the devices and functions necessary so as to cut in a precise and safe manner.
FALCON 302 is available as a bench model or eventually with the steel base. Furthermore it can be supplied with three-phase motor at one or two speeds.




A FEW FEATURES:

- Blade shaft assembled on spheroidal cast iron eccentric bushing.
- Bronze gear mounted with key and ring nut so as to grant the maximum hold.
- Worm screw shaft mounted on a pair of bushings.
- IP55 control handle.

- Clamping system by means of vice screw which slides on taper slide with adjustable gib.
- The front vice jaw has an axial adjustment so as to clamp the material as close as possible to the cutting line.
- Adjustable steel anti-burr device.
- Electric submerged pump at 48 V to lubricate blade.
- Double head return spring.
- Adjustable stop to make cuts of the same length.
- Machine predisposed to be hoisted.
- The machine is supplied without saw blade.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 01 - 02 - 05 - 24 - 25 - 64 - 71



Saw Blade	Power	Speed	Power	Speed	Cutting Length	Cutting Capacity							
						Ø	Circle	Square	Rectangle	Ø	Weight		
						0°	300	90	80	100x60	225	40	
HSS 300x32x2,5	1,5/1,8	45/90	0,75	45	105	45°	300	70	60	70x60	225	28	kg
						45°	300	70	60	70x60	225	28	130



FALCON

352 / 352 MA



FALCON 352, manual sawing machine to cut metals from 45° right to 45° left using an HSS blade. This high performance model has a heavy cast iron structure and is equipped with all the devices and functions necessary so as to cut in a precise and safe manner.

FALCON 352 is available as a bench model or eventually with the steel base, with a 2-speed three-phase motor. Furthermore upon request it can be supplied with an automatic vice (FALCON 352 MA, so that the vice closes automatically when lowering the head). In the MA version the machine is always supplied complete with steel base.

A FEW FEATURES:


- Motor insulation class IP54.
- Worm screw shaft mounted on a pair of bushings.
- Blade shaft assembled on two preloaded taper bearings on eccentric bushing.
- Externally adjustable clutch.
- Clamping system by means of vice screw which slides on taper slide with adjustable gib.

- Fixed burnished steel jaws.
- The front vice jaw has an axial adjustment so as to clamp the material as close as possible to the cutting line.
- Adjustable steel anti-burr device.
- Electric submerged pump at 48 V to lubricate blade.
- Double head return spring.
- Adjustable stop to make cuts of the same length.
- Stock support arm with roller predisposed to mount loading table.
- Machine predisposed to be hoisted.
- The machine is supplied without saw blade.
- Service keys and instructions manual for maintenance and spare parts list.




OPTIONALS FROM PAG 61 - N° 01 - 02 - 05 - 25 - 64 - 71

							∅				∅	
	kg	HSS mm	kW	rpm	mm							
FALCON						0°	350	115	100	130x80	250	50
352	220	350x32x2,5	1,1/2,2	30/60	130	45°	350	100	85	90x80	250	40
352MA	245					45°	350	75	75	90x65	250	40

FALCON 352



FALCON 352MA





COBRA

352 / 352 MA

COBRA 352, manual sawing machine to cut aluminium and light alloys using blade with electrowelded hard-metal plates. The machine cuts from 45° right to 45° left with the head which can be tilted from 0° to 45° left.

On the model 352 MA (pneumatic vice), which is supplied complete with steel base, the vices close automatically when lowering the head.



45°	50	50	160x35	180x20





A FEW FEATURES:

- Electric panel (wiring totally identifiable, main lockable disconnect switch, emergency stop, motor magne- to-thermal overload, minimum tension coil, protection against missing phase, low tension safety device 24 V).
- Rotating table mounted on bearing for a smooth and precise rotation.
- Adjustable mechanical stops at 0° and 45° left/right to position the head quickly.
- Screw locking system to lock the head at any degree.



- Steel base (for 352 MA only).
- Chip conveyor is predisposed to mount a chip collector.
- Automatic device to lubricate blade.
- Material is clamped by means of two vices which can be freely positioned along the longitudinal axis of the material.
- Movable aluminium jaws which can be adjusted vertically.
- Head locking system.
- Stock support arm with roller predisposed to mount loading table.

- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Machine predisposed to be hoisted.
- The machine is supplied without saw blade.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 06 - 31 - 39 - 62 - 64 - 71

COBRA	kg	mm	kW	rpm	kW	rpm	mm	0°	120	105	180x70	80
352	160	HM 350x32x3,4	2,2	3400	1,5/2,2	1700/3400	180	45°	120	100	135x60	55
352MA	210							45°	110	95	135x60	55





COBRA

352 SX EVO

COBRA 352 SX evo, semi-automatic electropneumatic sawing machine to cut aluminium and light alloys using blade with electrowelded hardmetal plates (HM).

- The machine cuts from 45° right to 45° left and the head tilts from 0° to 45° left so as to make inclined cuts.

- Sawing machine with controlled single axis microprocessor with the latest generation of controllers for semi-automatic sawing machines designed by MEP.

OPERATION: Starting the cycle by means of the relative push-button the following steps are carried out: - the vice closes and the motor starts - the head goes down to execute cut - motor stops - head returns to top position and vice opens.

- CICLE DOWN UP : Operating in semiautomatic cycle , the new function DOWN makes the head and blade motor stop once the cut is finished with the vice closed, by pressing the UP button the head raises back to its starting point and the vice opens.



45°	50	50	160x35	180x20



A FEW FEATURES:



- Display: 16 characters read on two lines so as to visualize technological parameters such as: + number of cuts carried out + cutting time + amperometer + diagnostics and/or caution messages (more than 100) visualized.
- Registration of alarms and events with the possibility to visualize the story of occurred events.
- Panel with low tension controls: polyester membrane keypad with tactile thermo-shaped buttons which give out an acoustic signal when pressed.

- The headstroke, according to the dimensions of the material which has to be cut, is set directly from the control panel.
- Rotating table mounted on bearing for a smooth and precise rotation.
- Material is clamped by means of two pneumatic vices which can be freely positioned along the longitudinal axis of the material.
- Adjustable mechanical stops at 0° and 45° left/right to position the head quickly.
- Chip conveyor predisposed to mount optional chip collector.

- Automatic device to lubricate the blade only when the machine is cutting.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- The machine is supplied without saw blade.
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-delivered traditional lubrication with emulsible oil.
- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 06 - 10 - 31 - 39 - 62 - 71



	mm	kW	rpm	mm	0°	120	105	180x70	80	kg
HM 350x32x3,4		1,5/2,2	1700/3400	180	45°	120	100	135x60	55	290
					45°	110	95	135x60	55	





COBRA

352 NC 5.0

COBRA 352 NC 5.0, automatic/semi-automatic electropneumatic CNC sawing machine to cut aluminium and light alloys using blade with electrowelded hard-metal plates (HM).

- The machine cuts from 45° right to 45° left and the head tilts from 0° to 45° left so as to make inclined cuts.

-CNC machine with a new controller : MEP 50 with Windows "CE" based. This new PLC has been specifically designed by MEP for the automation of its range of products.

A FEW FEATURES:

- Console with all centralized controls, installed on an articulated arm to follow the operator in every operating position for the controls and the EMERGENCY.

-7" touch screen display operator interface and push buttons for all functions of the sawing machine. It is simple and intuitive , it guarantees a reliable use and it controls all cutting parameters in real time



45°	50	50	160x35	180x20





- Registration of alarms and events with the possibility to visualize the story of occurred events.
- Bar feeder with recirculating balls screw/nut and stepper motor (feed in length in one stroke 600 mm, that can be repeated in order to cut any length).
- Panel with low tension controls: polyester membrane keypad with tactile thermo-shaped buttons which give out an acoustic signal when pressed.
- Cutting head and feeding vice positioning with joystick
- Automatic acquisition of the actual starting point of the cut
- Rotating table mounted on bearing for a smooth and precise rotation.



- Material is clamped by means of two pneumatic vices which can be freely positioned along the longitudinal axis of the material.
- Adjustable mechanical stops at 0° and 45° left/right to position the head quickly.
- Chip conveyor predisposed to mount optional chip collector (OPTIONAL).
- Shearing stress control.
- Pneumatic vertical vice.
- Automatic device to lubricate the blade only when the machine is cutting.
- Indicator with flashing light in case cycle is stopped.
- The machine is supplied without saw blade.
- Preset to be equipped with the spray mist system (OPTIONAL), as well as with the standard-

delivered traditional lubrication with emulsible oil.

- Service keys and instructions manual for maintenance and spare parts list.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 06 - 10 - 31 - 46 - 47 - 48 - 56 - 62 - 63 - 71



	mm	kW	rpm	mm						kg
HM 350x32x3,4		2,6/3,5	1700/3400	180	0°	120	105	180x70	80	600
					45°	120	100	135x60	55	
					45°	110	95	135x60	55	



SMV 3000





SMV 3000 READOUT MEASURING SYSTEM with maximum length 3000 mm.

FEATURES:

- Manual positioning by means of handwheel with length set visualized on control panel; resolution 0.1 mm.
- Encoder positioning transducer with setting tolerance ± 0.2 mm/1000mm (this value can vary though, according to how the stock is fed in manually to the mechanical stop).
- Pneumatic locking of stop during working cycle.
- Measuring device can be flipped over to clear roller table.
- Back-out of stop to pull away cut piece.

- Reinforced steelwork structure and steel carbon nitridated rollers.
- Single-phase or three-phase power supply.
- Instructions manual complete with spare parts list.



OPTIONALS FROM PAG 61 - N° 14 - 15 - 20

	BAR	mm	kg
SMV 3000	6	3000	345




SMV SMV 3000 PRO







SMV 3000 PRO, PROGRAMMABLE READOUT MEASURING SYSTEM with maximum length 3000 mm.

- FEATURES:
- Able to memorize max. 100 cutting programs.
 - Positioning by means of stepper motor, resolution 0.1 mm.
 - Movement with screw and nut with recirculating ballscrews.
 - Encoder positioning transducer with setting tolerance ± 0.2 mm/1000mm (this value can vary though, according to how the stock is fed in manually to the mechanical stop).
 - Visualization of alarm messages.
 - Measuring device can be flipped over to clear roller table.

- If the SMV 3000 PRO is connected to the machine, it executes:
- + piece counting + the sequence of 10 cutting programs of the 100 which are memorised + automatic back-out of stop to pull away cut piece.
- Reinforced steelwork structure and steel carbon nitridated rollers.
- Single-phase power supply.
- Instructions manual complete with spare parts list.



OPTIONALS FROM PAG 61 - N° 14 - 15 - 20

			
mm			kg
SMV 3000 PRO			400

OPTIONALS



Cut to measure stop with millimetered scale
0-600 mm




Emulsible oil Lt. 5




Spray mist system



Bi-metal band



Circular blade HSS



Circular blade HM



SHARK 281 - Cut Control System-Nachrüstsatz
(kit to retrofit)




SHARK 282 - Cut Control System (kit to
retrofit)



MA - Foot pedal control for vice




Supplementary foot pedal control w/
emergency stop




m/min 18/36 SHARK 281/282
m/min 20/40 SHARK 332/CCS/HYDRA/SXlevo



Electronic speed variator (inverter)




TIGER 352/352SXevo
rpm 30/60/90/180



Cod. 016 0855


SHARK 281
Adapter for SMV



Cod. 016 0907

TIGER COBRA
Adapter for SMV


16



Cod. 090 0800

SHARK 281
Adapter for unloading table


17



Cod. 090 0866


SHARK 281 NC 5.0
Adapter for unloading table

18



SHARK 330 NC 5.0
Adapter for unloading table


19



Cod. 090 0865

SHARK 330 NC 5.0 - Adapter for unloading
table for flip over stop R1,R2 o R3


20



Cod. 090 0861

SHARK 282/332/382 NC 5.0
Adapter for unloading table


21



Cod. 090 0864

SHARK 282/332/382 NC 5.0
Adapter for unloading table


22



Cod. 016 0885

SHARK 452-1
Adapter for loading table


23



Cod. 016 0884

SHARK 452-1
Adapter for unloading table


24



Cod. 016 0866

FALCON 302
Adapter for loading table


25



Cod. 016 0867

FALCON 302/352
Adapter for unloading table


26



Cod. 090 0863

TIGER 352/372
Adapter for unloading table


27



Cod. 016 0901

PH 211-1
Adapter for loading table


28



Cod. 016 0896

PH 211-1
Adapter for unloading table


29



Cod. 016 0903

PH 261-1
Adapter for loading table

30




Cod. 016 0902

PH 261-1
Adapter for unloading table

OPTIONALS

31



Cod. 016 0868

COBRA 352
Adapter for unloading table

32



SHARK SXI evo
Hydraulic vice pressure adjuster

33



SHARK NC 5.0
Hydraulic vice pressure adjuster

34



Shark 281/282
Laser projector + work light

35



SHARK 332 NC 5.0
Special vice to reduce restpiece

36



Device for bundle cutting w/guide to unload
pieces cut (max 240x90 mm)

37




Adjustable guide to unload pieces cut

38




Shark 332/382/452-1 CCS HYDRA
Hydraulic vice

39




TIGER 352MA/COBRA 352MA
Pneumatic vertical vice

40



TIGER 352 NC 5.0
Special vice to reduce restpiece

41



TIGER 352 NC 5.0 max 70x70
set of comb jaws for bundle cutting

42




TIGER 352 NC 5.0 - Set of comb jaws when
equipped w/restpiece reduction min.
(max 70x70 mm)

43




TIGER 352MA/SXevo/NC 5,0
TIGER 372 SXevo
Supplementary pneumatic vice

44



TIGER 352 MA/SXevo TIGER 372 SXevo
Rahmen set of jaws for H=50 frames

45




TIGER 352 MA/SXevo TIGER 372 SXevo
Rahmenprofile set of jaws for H=60 mm
frames



46
COBRA 352 NC 5.0
Special vice to reduce restpiece




47
COBRA 352 NC 5.0 - set of comb jaws in teflon for bundle cutting (max mm 75x75)




48
COBRA 352 NC 5.0 - Set of comb jaws when equipped w/restpiece reduction min. (max 70x70 mm)




49
SHARK 281 NC 5.0 - Hydraulic vertical vices for bundle cutting (max 170x130 mm)



50
SHARK 282 NC 5.0 - Hydraulic vertical vices for bundle cutting (max 170x130 mm)




51
SHARK 330 NC 5.0 - Hydraulic vertical vices for bundle cutting (max 320x160 mm)



52
SHARK 332 NC 5.0 - Hydraulic vertical vices for bundle cutting (max 320x160 mm)



53
SHARK 230 NC HS 5.0 - Hydraulic vertical vices for bundle cutting (max 230x230 mm)



55
SHARK 332 SXI/NC 5.0 - Motorized wire chip brush



56
loading table for comb jaws (componible modules 1500 mm)



57
two sets of vertical rollers for roller table with covering K110



58
two sets of vertical rollers for roller table with covering K110HD



59
SB100 - Stock support



60
Powered chip conveyor


OPTIONALS



SHARK 230 NC 5.0
Powered chip auger




Chip collector




COBRA NC 5.0
Double suction system



Steel base



SHARK 332/382/452-1 CCS HYDRA
Digital Angle Display



SHARK 332/452-1 SXlevo
Cutting angle displaying




SMV 3000




SMV 3000 PRO



SHARK 230 NC HS 5.0
Front split vise




SHARK 331 NC 5.0 spider - Hydraulic vertical
vices for bundle cutting
(max 320x150 mm)




FLIP OVER STOPS' MODELS


	K40	K110	K110HD	K210
R1	●	●		
R2	●	●		●
R3	●	●		●



- R1 FLIP OVER STOP (light version): it can be mounted on K40 and K110 roller tables offside.
- It can be raised so as to move the bar along.
 - It slides on two aluminium guides with teflon slides.
 - The rod is engraved on an aluminium bar.



- R2 FLIP OVER STOP (medium version): it can be mounted on K40, K110, K210 and K250 roller tables offside.
- It can be raised so as to move the bar along.
 - It slides on two horizontal guides with teflon slides.
 - The rod is engraved on an aluminium bar.
 - Measure visualization enlarged by a magnifying glass.







- R3 FLIP OVER STOP (strong version): it can be mounted K40, K110, K210 and K250 roller tables offside.
- Made of casting and steel.
 - It can be raised so as to move the bar along.
 - It slides on a horizontal steel linear guide with recirculating ballscrews.
 - The rod is engraved on an aluminium bar.
 - Measure visualization enlarged by a magnifying glass.



STOP AND MEASURING ROD

R1	R2	R3
K40	K110	K210
K110 HD		



MODELLO	∅ mm	kg	A	P	Nr. x L	kg x L	H ÷ H¹
K 40	24	40	190	245	7	280 X 1500	735 ÷ 1070
K 110	32	110	330	360	6	660 X 1500	618 ÷ 908
K 210	35	210	460	490	6	1260 X 1500	620 ÷ 915
K 110 HD	50	250	340	371	6	1500 X 1514	840 ÷ 910

ROLLER TABLES



71



K40

72



K110

73










K110 HD

74



K210

		Minimum out of stock (in mm)	Minimum cutting length (in mm)	Speed of feeding vice (m/ min)	Max weight that the feeding vice can pull (kg)	Height of working table (mm)	Cutting capacity with overhead bundling (mm)	Capacity Of The Coolant Tank (Lt)	Capacity of the hydraulic tank (Lt)	Blade length (min/max)
BANDSAWING MACHINES										
	PH 211/1	-	-	-	-	935	-	10	-	2130 ±20 X 20 X 0,9
	PH 211/1 - HB	-	-	-	-	935	-	10	-	2130 ±20 X 20 X 0,9
	PH 261/1	-	-	-	-	950	-	15	-	2450 ±27 X 27 X 0,9
	PH 261/1 - HB	-	-	-	-	950	-	15	-	2450 ±27 X 27 X 0,9
	SHARK 281	-	-	-	-	870	-	13	-	2950 ±20 X 27 X 0,9
	SHARK 281 CCS	-	-	-	-	870	-	13	-	2950 ±20 X 27 X 0,9
	SHARK 281 SXI evo	-	-	-	-	875	-	13	2,5	2950 ±20 X 27 X 0,9
	SHARK 281 NC 5.0	260	10	9	1360	870	max 170X130	120	35	2950 ±20 X 27 X 0,9
	SHARK 282	-	-	-	-	870	-	13	-	2950 ±20 X 27 X 0,9
	SHARK 282 CCS	-	-	-	-	870	-	13	-	2950 ±20 X 27 X 0,9
	SHARK 282 SXI evo	-	-	-	-	861	-	13	2,5	2950 ±20 X 27 X 0,9
	SHARK 282 NC 5.0	300	12	9	1360	870	max 170X130	120	35	2950 ±20 X 27 X 0,9
	SHARK 330 NC 5.0	80	10	9	1360	870	max 320X160	120	35	3320 ±20 X 27 X 0,9
	SHARK 331 NC 5.0 spider	-	-	9	1360	900	max 320X150	100	35	3320 ±20 X 27 X 0,9
	SHARK 332 CCS	-	-	-	-	870	-	60	-	3320 ±20 X 27 X 0,9
	SHARK 332 CCS hydra	-	-	-	-	870	-	60	2,5	3320 ±20 X 27 X 0,9
	SHARK 332 SXI evo	-	-	-	-	870	-	60	2,5	3320 ±20 X 27 X 0,9
	SHARK 332 NC 5.0	400	10	9	1360	870	max 320X160	120	35	3320 ±20 X 27 X 0,9
	SHARK 382 CCS hydra	-	-	-	-	870	-	60	2,5	3440 ±20 X 27 X 0,9
	SHARK 382 SXI evo	-	-	-	-	870	-	60	2,5	3440 ±20 X 27 X 0,9
	SHARK 452-1 CCS	-	-	-	-	870	-	80	-	4500 ±20 X 34 X 0,9
	SHARK 452-1 CCS hydra	-	-	-	-	870	-	80	2,5	4500 ±20 X 34 X 0,9
	SHARK 452-1 SXI evo	-	-	-	-	870	-	80	2,5	4500 ±20 X 34 X 0,9
	SHARK 230 NC HS 5.0	70	10	9	1360	870	230X230	95	27	2950 ±20 X 27 X 0,9

		Minimum out of stock (in mm)	Minimum cutting length (in mm)	Speed of feeding vice (m/ min)	Max weight that the feeding vice can pull (kg)	Height of working table (mm)	Cutting capacity with overhead bundling (mm)	Capacity Of The Coolant Tank (Lt)	Capacity of the hydraulic tank (Lt)	Blade specification (mm)	
VERTICAL SAWING MACHINES FOR METALS 	TIGER 352/MA	-	-	-	-	950	-	20	-	HSS 350 X 32 X 2,5	
	TIGER 352 SX evo	-	-	-	-	950	-	20	-	HSS 350 X 32 X 2,5	
	TIGER 352 NC 5.0	320	10	9	1360	950	-	20	-	HSS 350 X 32 X 2,5	
	TIGER 372 SX evo	-	-	-	-	950	-	80	-	HSS 370 X 32 X 3	
PIVOT SAWING MACHINES FOR METALS 	WILLY 225	-	-	-	-	-	-	2	-	HSS 225 X 32 X 1,9	
		FALCON 251	-	-	-	-	995	-	4,5	-	HSS 250 X 32 X 2
		FALCON 302	-	-	-	-	928	-	2,5	-	HSS 27 X 32 X 2,5
FALCON 352/MA		-	-	-	-	970	-	4,2	-	HSS 350 X 32 X 2,5	
PIVOT SAWING MACHINES FOR ALUMINIUM 	COBRA 352/MA	-	-	-	-	940	-	1/10	-	HM 350 X 32 X 3,4	
	COBRA 352 SX evo	-	-	-	-	940	-	1/10	-	HM 350 X 32 X 3,4	
	COBRA 352 NC 5.0	385	-	9	1360	940	-	1/10	75X75	HM 350 X 32 X 3,4	
MEASURING SYSTEM 	SMV 3000					850÷970					
	SMV PRO					850÷970					

GENERAL SALES CONDITIONS

1 - DEFINITIONS

“CGV”: these general sales conditions, whose following terms shall have the meaning given below;

“Mep” and/or “company”: Mep S.p.a. with administrative office in Pergola (PU);

“Customer”: any company, body or legal entity purchasing Mep products;

“Products”: goods produced and/or marketed by Mep;

“Order/s”: each product purchase proposal sent to Mep by the customer;

“Sale/s”: each sale contract closed between Mep and the customer following the written acceptance sent by Mep to the customer;

“Brands”: all brands Mep is owner or licensee of;

“Intellectual property rights”: all Mep intellectual and industrial property rights, registered or not, as well as any application or registration concerning these rights and any other right or protection.

“Conditions” mean all contract agreements, terms and conditions as a whole included in these General sales conditions (CGV).

2 - PURPOSES

2.1 These CGV apply to all product sales. In case of conflict between the conditions and terms of these CGV and the terms and conditions agreed for a single sale, the latter shall prevail.

2.2 Mep reserves the right to add, modify or cancel any provision of these CGV, being it understood that all changes shall apply to the sales closed from the thirtieth day after the transmitted notice, also by e-mail or fax, by Mep to the customer.

3 - ORDERS AND SALES

3.1 Each sale shall be ruled exclusively by these mandatory CGV unless different agreements have already been signed between Mep and customer.

3.2 Orders shall be binding for Mep if accepted in writing with order confirmation, sent to the customer also by e-mail or fax.

3.3 Should the customer receive a written

confirmation by Mep containing terms other than those included in the order, the sale shall be considered closed under the terms of the confirmation if the customer does not object to it within five days from receiving the order confirmation.

3.4 The company can immediately start fulfilling the received orders. The supply delivery to the carrier or shipping agent, together with the order acceptance notice, represents the start of the fulfillment, for the purposes and effects of art. 1327 of the Italian Civil Code.

4 - PRICES

4.1 The prices of the products, to be meant as VAT excluded, shall be those listed in the company price list in force when the order is forwarded, namely those indicated by the company in the single order confirmations for the products not included in the price list.

5 - DELIVERIES

5.1 Mep shall deliver the products ex works at his factories of Pergola, unless a different written agreement. If required, Mep shall entrust carriers with the transport at risk, costs and expenses of the customer.

5.2 The company may carry out the supply with partial deliveries; in this case, each delivery shall be considered as specific sale performance.

5.3 Possible irregularities or lacks in the supplies shall be claimed in writing to the carrier at the delivery and communicated to the company within max. three working days.

5.4 Within 20 days before the expected delivery date of the products the company and the customer can cancel or suspend the supply due

to force majeure or due to reasons out of control, with mutual exemption to damages, for example such as, but not limited to:

a) strikes, even partial, power cut-off, natural disasters, measures by public authorities, problems in transports, riots;

b) problems connected with the production or the order planning;

c) difficulty in getting raw material supplies.

In case of order cancellation by the customer of non-standard products, the company shall

be entitled to receive the payment of what suitably realized till the communication was received.

6 - GUARANTEES

6.1 The company guarantees that each product complies with the specifications indicated in the catalogue, standard tolerance excepted.

6.2 The company can anyway modify the products, even without informing the customers, reasonably in their technical characteristics, design, materials and finishes as deemed necessary and/or suitable; the customer, therefore, cannot claim or reject, nor even partially, the supply due to such reasonable changes.

6.3 The company guarantees that the products are free of defects and/or faults for a period of one year from the date of delivery to the customer.

6.4 Possible defects or faults shall be communicated by the customer within thirty days from receiving the supply and/or discovering them, if hidden, otherwise the right lapses. Damages cannot be claimed to the company for possible delays in repairs and/or replacements within the two months after the communication.

6.5 The company's responsibility for the supplies of products and for their use is anyway limited to the cost for repairing faults and/or defects of the products or for replacing them.

6.6 Customers are not entitled to return products without a previous written authorization by the company.

6.7 The customer guarantees that the products shall be used according to the instructions of the company and engages to inform all operators involved in their use that the company is ready and available to give all information aimed at the correct operation and safety of the products.

7 - PAYMENTS

7.1 The customer shall pay the invoices issued by the company for the collection of the performed supplies in compliance with the terms indicated in the order confirmation.

7.2 The company shall issue invoices for every product supply, even in case of partial supplies referred to the same order confirmation.

7.3 In case of delayed payment vs. the contract

terms, the customer shall pay to the company default interests according to the Italian law decree of 9th October 2002 no. 231, as well as the refund of the collection costs.

7.4 For invoices issued with indication of payment instalments, failure to pay even a single instalment shall involve the automatic acceleration clause and the company shall be entitled to ask immediately for the whole credit, increased of default interests.

8 - PROPERTY RIGHTS

8.1 The customer cannot use the products or part of them or any description or drawing, even if not specifically protected by a patent or registered trademark, to design or manufacture similar products, unless he has obtained the previous written authorization by the company; in this case, too, all patents, registered designs, trademarks, copyrights and intellectual property rights concerning or connected with the products remain the full and exclusive property of the company and the customer shall adopt the strictest confidentiality accordingly.

9 - EXPRESS RESOLUTIVE CLAUSE

9.1 The company is entitled to cancel at any time, according to art. 1456 of the Italian Civil Code, by written communication sent to the customer, the sale/s in case of non-fulfillment of the obligations of articles : 6 (payments); 7 (intellectual property rights).

10 - APPLICABLE LAW - COMPETENT COURT

10.1 Any controversy arising on the closing, performance or resolution of the contract, or possible damage due to the products or their use, is ruled by the Italian law and subject to the Italian ordinary courts; by way of exception to any other law or conventional principle, the court of Pesaro - Fano detached department shall be exclusively competent as for territory.



WHERE TO FIND US

MEP SPA
 via Enzo Magnani, 1
 61045 Pergola (PU) Italy
 tel: +39 - 0721 - 73721
 fax: +39 - 0721 - 734533
 mepsa@mepsaws.it
 http://www.mepsaws.it

Capitale Sociale
 Eur 10.372.791,00 int. vers.
 Reg. Imprese Milano 13051480153
 Cod fiscale, partita IVA 13051480153

DEALER

The manufacturer reserves the right to carry out modifications without notice.



www.mepsaws.it

MEP SPA
PERGOLA ITALIA

Via Enzo Magnani, 1 - 61045 Pergola (PU) Italy

Tel: +39-0721-73721
E-mail: mepsa@mepsaws.it
PEC: mepsa@mepsaws.legalmail.it