



SHARK 281

SHARK 281, manual band sawing machine to cut from 0° to 60° left.

The vice on the pneumatic versions (MA) opens and closes by means of a manually operated valve (or by means of a footpedal which is instead optional).

A FEW FEATURES:

- Electric panel (wiring totally identifiable, stand-by, loose-key safety switch, main switch, pole change switch, emergency stop, motor magneto-thermal overload, minimum tension coil, protection against missing phase, low tension safety device (LTSD 24 V).- IP55 control handle.
- Vice with fast clamping device.




SHARK 281/281CCS



SHARK 281/281CCS



- Hydraulic transducer to visualize band tensioning.
- Electric pump for band lubrication and cooling.
- Wire chip brush for band cleaning.
- Double head return spring.
- Adjustable rod to measure stop to make cuts of the same length with millimetred steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.
- The CUT CONTROL SYSTEM (CCS) can be retrofitted on machines out in the field.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 07 - 09 - 11 - 16 - 72

mm	kW	m/min	mm	0°	45°	60°	kg
				250	190	120	
2950x27x0,9	1,5/1,8	36/72	285	230	180	110	370