



SHARK 282





SHARK 282, manual band sawing machine to cut from 45° right to 60° left.

The vice on the pneumatic versions (MA) opens and closes by means of a manually operated valve (or by means of a footpedal which is instead optional).

A FEW FEATURES:

- Hydraulic transducer to visualize band tensioning.
- Wire chip brush for band cleaning.
- Double head return spring.
- Sliding vice with sideways movement and fast-positioning system.
- Wide working surface with rotating table installed on a roller bearing, dia. 265 mm, pre-loaded with thrust bearing.

- Adjustable precision stops for cuts at 0°, 45°, 60° left and 45° right.
- Steel base with removable coolant tray.
- Electric pump for band lubrication and cooling.
- Machine arranged for handling with movement equipment.
- Adjustable rod to measure stop to make cuts of the same length with millimetric steel rod.
- Stock support arm with roller predisposed to mount loading table.
- Bi-metal band for solids and sections.
- Service keys and instructions manual for maintenance and spare parts list.
- The CUT CONTROL SYSTEM (CCS) can be retrofitted on machines out in the field.



SHARK 282/282CCS

OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 08 - 09 - 11 - 20 - 34 - 72

Saw Blade	Power	Speed	Cutting Depth	Cutting Capacity			Weight
				0°	45°	60°	
2950x27x0,9	1,5/1,8	36/72	285	250	230	120	440
				220	200	80	
				280x220	220x200	140x80	
				200	170	200x140	